

Shallow Shell™ SSTC60

Poliestireno Gel, Resina Catiónica
Fuertemente ácida, Forma de sodio,
Tecnología Shallow Shell™*

PRINCIPALES APLICACIONES

- Ablandamiento - Industrial
- Desmineralización cuando regenerado con ácidos

VENTAJAS

- SST shorter diffusion path benefits:
- Highest regeneration efficiency
- Very low leakage
- Highly resistant to iron fouling
- Lower rinse volumes
- Lower operating costs
- Excellent physical/chemical stability

SISTEMAS

- Sistema Cocorrente de regeneración
- Sistemas de Regeneración Contracorrente

APROBACIONES REGULADORAS

- Certificado por la WQA, estándar NSF ANSI 61

ENVASE TÍPICO

- Bolsa de 1 pie³
- Bolsa de 25 L
- Tambor (fibra) de 5 pie³
- Supersack de 1 m³
- Supersack de 42 pie³

* SST® es una marca registrada de Purolite Corporation.

CARACTERÍSTICAS FÍSICAS Y QUÍMICAS:

Estructura del polímero	Gel reticulado poliestireno con divinilbenceno
Aspecto	Esferas
Grupo funcional	ácido sulfónico
Forma iónica	Na ⁺ forma
Capacidad de peso seco (min.)	3.8 EQ/kg (Na ⁺ forma)
Retención de la humedad	38 - 46 % (Na ⁺ forma)
Rango de tamaño de esferas	300 - 1200 µm
< 300 µm (max.)	1 %
Coefficiente de uniformidad (max.)	1.7
Hinchamiento reversible, Na ⁺ → H ⁺ (max.)	8 %
Densidad específica	1.2
Peso de envío (aprox.)	775 - 825 g/L (48.4 - 51.6 lb/pie ³)
Límite de temperatura	60 °C (140.0 °F)



Algeria
Australia
Bahrain
Brazil
Canada
China

India
Indonesia
Israel
Italy
Japan
Jordan

Mexico
Morocco
New Zealand
Poland
Romania
Russia

Spain
Taiwan
Tunisia
Turkey
UK
Ukraine
USA
Uzbekistan

Czech Republic
France
Germany

Kazakhstan
Korea
Malaysia

Singapore
Slovak Republic
South Africa



Americas

Purolite
2201 Renaissance Blvd.
King of Prussia, PA 19406
T +1 800 343 1500
T +1 610 668 9090
F +1 800 260 1065
americas@purolite.com

EMEA

Purolite Ltd.
Unit D
Llantrisant Business Park
Llantrisant, Wales, UK
CF72 8LF
T +44 1443 229334
F +44 1443 227073
emea@purolite.com

FSU

Purolite Ltd.
Office 6-1
36 Lyusinovskaya Str.
Moscow, Russia
115093
T +7 495 363 5056
F +7 495 564 8121
fsu@purolite.com

Asia Pacific

Purolite China Co. Ltd.
Room 707, C Section
Huanglong Century Plaza
No.3 Hangda Road
Hangzhou, Zhejiang, China 310007
T +86 571 876 31382
F +86 571 876 31385
asiapacific@purolite.com

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Purolite expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The



information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.